


Aspen 937



Metal Halide

70w	MHE	E27	PN937	B	MHE070	-	+	160
150w	MHE	E27	PN937	B	MHE150	-	+	160
250w	MHE	E40	PN937	B	MHE250	-	+	161



Current and Power Ratings

Lamp	Watts (W)	□ B	
		Line 1 (A)	pfc Cap
1x 70W	81.5	0.43	12uf
1x 150W	168.5	0.80	20uf
1x 250W	285.5	1.35	32uf



Wire wound



1 - White 3 - Black 6 - Graphite



306 Wire guard
307 5m Suspension (wire only)

Recommended Lamps

Type	4300K	
	Osram	Philips
MHE070	H70EN	-
MHE150	H15EN	-
MHE250	H250EN	181145

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg