

Aspen Prismatic




Fluorescent

32w	PLT	GX24q3	PN938	-	PLT032	-	+	162
42w	PLT	GX24q4	PN938	-	PLT042	-	+	162
70w	PLT	GX24q6	PN938	D	PLT070	-	+	163
60w	PLH	2G8	PN938	D	PLH060	-	+	165
85w	PLH	2G8	PN938	D	PLH085	-	+	165

Metal Halide

70w	MHE	E27	PN938	B	MHE070	-	+	059
150w	MHE	E27	PN938	B	MHE150	-	+	059
250w	MHE	E40	PN938	B	MHE250	-	+	059
70w	MHS	G12	PN938	B	MHS070	-	+	060
150w	MHS	G12	PN938	B	MHS150	-	+	060



□ Gear types F & G must be operated through a Digital Serial Interface (p371)

B	Wire wound
D	High frequency
E	High frequency + Emergency
F	High frequency digital dimming
G	High frequency digital dimming + Emergency
H	High frequency analogue (1-10V) dimming
I	High frequency analogue (1-10V) dimming + Emergency
J	High frequency switch dimming
K	High frequency switch dimming + Emergency

1 - White 3 - Black 6 - Graphite

+	Glass
309	Safety clear (PLT/PLH)
307	5m Suspension (wire only)

Current and Power Ratings

Lamp	Watts (W)	Line 1 (A)
1x 32W	35.0	0.17
1x 42W	46.0	0.22
1x 70W	77.0	0.35

Lamp	Watts (W)	Line 1 (A)
1x 60W	63.0	0.30
1x 85W	91.0	0.40

Lamp	Watts (W)	Line 1 (A)	pfc Cap
1x 70W	81.5	0.43	12uf
1x 150W	168.5	0.80	20uf
1x 250W	285.5	1.35	32uf

Lamp	Watts (W)	Line 1 (A)	pfc Cap	Watts (W)	Line 1 (A)
1x 70W	81.5	0.43	12uf	79.5	0.36
1x 150W	168.5	0.80	20uf	162.0	0.70

Add 12W to Emergency versions for continuous charge

Recommended Lamps

Type	3000K		4000K	
	Osram	Philips	Osram	Philips
PLT032	DTE323	625519	DTE324	625526
PLT042	DTE423	763952	DTE424	763976
PLT070	TEN703	-	TEN704	-

Type	3000K		4000K	
	Osram	Philips	Osram	Philips
PLH060	-	264077	-	264091
PLH085	-	264114	-	264237

Type	4300K	
	Osram	Philips
MHE070	H70EN	-
MHE150	H15EN	-
MHE250	H250EN	181145

Type	3000K		4200K	
	Osram	Philips	Osram	Philips
MHS070	H70W	-	H70N	-
MHS150	H150W	-	H150N	-

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg