



Montage Delux

Montage Floating Glass

Eclipse

Network Ports

Downlighters

LV Halogen

Power	Lamp	Socket	Mounting	Model	Control	Dimmer	Emergency
50w	LVH	GX5.3	Montage Delux	NW542	-	LVH050	-
50w	LVH	GX5.3	Montage Floating Glass	NW543	-	LVH050	+
50w	LVH	GX5.3	Eclipse	NW864	-	LVH050	+

MV Halogen

50w	MVH	GZ10	Eclipse	NW864	A	MVH050	-	+
-----	-----	------	---------	-------	---	--------	---	---

Metal Halide


35w	MHB	GX10	Eclipse	NW864	Q	MHB035	-	+
-----	-----	------	---------	-------	---	--------	---	---

Current and Power Ratings

Lamp	Watts (W)	Line 1 (A)
1x 50W	55.0	0.22

Lamp	Watts (W)	Line 1 (A)
1x 50W	50.0	0.21

Lamp	Watts (W)	Line 1 (A)
1x 35W	44.5	0.22



Recommended Lamps

Type	Osram	Philips
LVH050	M258T	425164


Type	Osram	Philips
MVH050	P165FD	411792

Type	Sylvania
MHB035	0020270





























- A** No control gear 240V (MVH)
- M** Electronic dimmable transformer
- N** Electronic dimmable transformer + Emergency
- Q** Electronic discharge ballast (MHB)

- 1** - White **3** - Black **6** - Graphite

- 002** Glass Halo blue



002 Halo blue

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg