


Network Modules

Spacers





















Components						
Spacer Module	135mm	0.5kg	NW135	X	NSM000	-
Spacer Module	165mm	0.7kg	NW136	X	NSM000	-
Spacer Module	300mm	1.2kg	NW133	X	NSM000	-
Spacer Module	600mm	2.4kg	NW100	X	NSM000	-
Spacer Module	900mm	3.6kg	NW101	X	NSM000	-
Spacer Module	1200mm	4.7kg	NW102	X	NSM000	-
Spacer Module	1500mm	5.9kg	NW103	X	NSM000	-
Spacer Module	1800mm	7.1kg	NW104	X	NSM000	-



X Non electrical component



1 - White 3 - Black 6 - Graphite

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg