

Network Uplighter Modules

Tallis

Fluorescent						
40w	PLL	2G11	NW147	PLL040	+	133
55w	PLL	2G11	NW147	PLL055	+	134
2x 40w	PLL	2G11	NW147	PLL240	+	135
2x 55w	PLL	2G11	NW147	PLL255	+	136



PLL

- High frequency
- High frequency digital dimming
- High frequency analogue (1-10V) dimming
- High frequency switch dimming

- 1 - White 3 - Black 6 - Graphite





























Glass
087 Etched

Current and Power Ratings

Lamp	D, F, H, J	
	Watts (W)	Line 1 (A)
1x 40W	44.0	0.20
1x 55W	60.0	0.28
2x 40W	87.0	0.40
2x 55W	120.0	0.54

Recommended Lamps

Type	3000K		4200K	
	Osram	Philips	Osram	Philips
PLL040	DL4083	610942	DL4084	610973
PLL055	DL5583	615411	DL5584	615428

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg