

Network Downlighter Modules

Teev - 1500mm Modules

Fluorescent							
28w	TFL	G5	NW145	TFL028		+	130
54w	TFL	G5	NW145	TFL054	-	+	130

240V 50Hz	Class 1	IP 20	20mm	0.5 m	T5A
	D,F,H,J	E,G,I,K			
Max	7.9 kg	8.9 kg			

TFL

Current and Power Ratings

Lamp	Watts (W)	D-K Line 1 (A)
1x 28W	33.0	0.16
1x 54W	58.0	0.27

Recommended Lamps


Type	3000K		4200K	
	Osram	Philips	Osram	Philips
TFL028	FQ2883	639462	FQ2884	639486
TFL054	FQ5483	637345	FQ5484	637406





























Gear types F & G must be operated through a Digital Serial Interface (p371)

D	High frequency
E	High frequency + Emergency
F	High frequency digital dimming
G	High frequency digital dimming + Emergency
H	High frequency analogue (1-10V) dimming
I	High frequency analogue (1-10V) dimming + Emergency
J	High frequency switch dimming
K	High frequency switch dimming + Emergency

1 - White 3 - Black 6 - Graphite

	Glass	
084	Etched	129
085	Etched squares	129
086	Square louvre	131



	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg