


Ascension Pendant



Fluorescent

2x 40w TFL	2GX 13	PN948	TFL240	155
2x 55w TFL	2GX 13	PN948	TFL255	155



TFL

□ Gear types F & G must be operated through a Digital Serial Interface (p371)

- D** High frequency
- E** High frequency + Emergency
- F** High frequency digital dimming
- G** High frequency digital dimming + Emergency
- H** High frequency analogue (1-10V) dimming
- I** High frequency analogue (1-10V) dimming + Emergency
- J** High frequency switch dimming
- K** High frequency switch dimming + Emergency

● 1 - White 3 - Black 6 - Graphite





























Current and Power Ratings

Lamp	□ D-K	
	Watts (W)	Line 1 (A)
2x 40W	92.0	0.40
2x 55W	120.0	0.54

Add 12W to Emergency versions for continuous charge

Recommended Lamps

Type	3000K		4200K	
	Osram	Philips	Osram	Philips
TLF040	FC4083	640970	FC4084	642233
TLF055	FC5583	642790	FC5584	642516

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg