

## Breeze Free Standing



### Fluorescent

2x 40w	PLL	2G11	UP636	PLL240	+	067
2x 55w	PLL	2G11	UP636	PLL255	+	067



PLL

Gear type F must be operated through a Digital Serial Interface (p371)

- D** High frequency
- F** High frequency digital dimming
- H** High frequency analogue (1-10V) dimming
- J** High frequency switch dimming

1 - White 3 - Black 6 - Graphite

139 Tilt switch





























### Current and Power Ratings

Lamp	D-J	
	Watts (W)	Line 1 (A)
1x 40W	44.0	0.20
1x 55W	60.0	0.28

Add 12W to Emergency versions for continuous charge

### Recommended Lamps

Type	3000K		4000K	
	Osram	Philips	Osram	Philips
PLL040	DL4083	610942	DL4084	610973
PLL055	DL5583	615411	DL5584	615428

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	<b>Uplighting</b> / Downlighting
	Uplighting / <b>Downlighting</b>
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg