

## Ported Eclipse Suspended



### LV Halogen

2x 50w LVH	GX5.3	Duet	BS864	M	LVH050	-	+
3x 50w LVH	GX5.3	Trio	CS864	M	LVH050	-	+

### MV Halogen


2x 50w MVH	GZ10	Duet	BS864	A	MVH050	-	+
3x 50w MVH	GZ10	Trio	CS864	A	MVH050	-	+

### Metal Halide

2x 35w MHB	GX10	Duet	BS864	Q	MHB035	-	+
3x 35w MHB	GX10	Trio	CS864	Q	MHB035	-	+

240V 50Hz	Class MH 1 MHB 1 LVH 1	IP 20	90°	350°		
--------------	------------------------	-------	-----	------	--	--

1 m	Duet	Trio
Max	2.5 kg	3.8 kg



### Current and Power Ratings

Lamp	M	
	Watts (W)	Line 1 (A)
1x 50W	55.0	0.22

Lamp	A	
	Watts (W)	Line 1 (A)
1x 50W	50.0	0.21

Lamp	Q	
	Watts (W)	Line 1 (A)
1x 35W	44.5	0.22





























### Recommended Lamps

Type	Osram	Philips
LVH050	M258T	425164

Type	Osram	Philips
MVH050	P165FD	411792

Type	Sylvania
MHB035	0020270

- A** No control gear 240V
- M** Electronic dimmable transformer
- Q** Electronic discharge ballast
- 1** - White   **3** - Black   **6** - Graphite   **7** - White/Graphite
- 8** - Graphite/Black (Shown)   **9** - Black/Graphite
- 083** 4x 5m Suspensions (wires only)

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	<b>Uplighting</b> / Downlighting
	Uplighting / <b>Downlighting</b>
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg