




## Tana

<b>MV Halogen</b>				
<b>Surface</b>				
100w	MVR	E27	MS726	A MVR 100
<b>Single Circuit Track</b>				
100w	MVR	E27	TS726	A MVR 100
<b>Three Circuit Track</b>				
100w	MVR	E27	TT726	A MVR 100



--	--	--	--	--	--	--	--	--	--

MVR (Par 30)



No control gear 240V

1 - White 3 - Black 6 - Graphite

### Current and Power Ratings

Lamp	A	
	Current (A)	Current (A)
1x 100WV	0.43	100.0

### Recommended Lamps

Type	Osram	Philips	Sylvania
MVR100	---	518811	0021237

## Product Codes Explained



## Symbols

	12V
	Voltage & frequency
	Class I / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Unfused terminal block
	Fused terminal block
	Integral fuse
	Knockout size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	<b>Uplighting</b> / Downlighting
	Uplighting / <b>Downlighting</b>
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Injection moulding
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg