

Aqua Splash Resistant








LV Halogen

50w LVH GX5.3 1D559 LVH050

12V ID559P	240V 50Hz	ID559M ID559P	IP 64	F	104mm Ø
Class 1I	1II				
Q--I 0.5 m	Y	Max	M 0.4 kg	N 4.7 kg	P 0.3 kg
				N T5A	


LVH 

Current and Power Ratings

Lamp	M	
	Watts (W)	Line 1 (A)
1x 50W	55.0	0.22

Recommended Lamps

Type	Osram	Philips
LVH050	M258T	425164

- Electronic dimmable transformer
 - Electronic dimmable transformer + Emergency
 - 240/12V Transformer required
- 
1 - White
3 - Black
4 - Chrome
6 - Graphite

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg