



Arill Adjustable TriColor

LV Halogen

3x 50w LVH GX5.3 1D892 M LVH050 - +

240V 50Hz Class 1 IP 20 F 60° 356° 177 mm Ø G--I 1 m 2.2 kg

LVH

Lighting Controller

Modulator

CD811 A MOD010

108 x 194 mm

- A No control gear 240V
- M Electronic dimmable transformer
- 1 - White 3 - Black 6 - Graphite
- Glass filters
- 213 3x Red
- 214 3x Green
- 215 3x Blue
- 216 1x Red 1x Green 1x Blue (Shown)

Low Voltage DICMROIC lamps must not be used in this luminaire. Reflector lamps only

Current and Power Ratings

Lamp	□ ■ M	
	Watts (W)	Line 1 (A)
1x 50W	55.0	0.22

Recommended Lamps

Type	Osram	Phillips
LVH050	M58A	-

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg