

Kava Tilt



Metal Halide

20w	MHC	G8.5	1D881	Q	MHC020	-	+	183
35w	MHC	G8.5	1D881	Q	MHC035	-	+	183
70w	MHC	G8.5	1D881	Q	MHC070	-	+	183




MHC

- B Wire wound
- Q Electronic discharge ballast

1 - White 3 - Black 6 - Graphite

- Reflector
- 079** Narrow beam angle (MHC) 140
- +** Food enhancement filters (p373)



Wide beam supplied as standard

Current and Power Ratings

Lamp	Watts (W)	Line 1 (A)
1x 20W	23.8	0.10
1x 35W	44.5	0.20
1x 70W	79.5	0.36

Recommended Lamps

Type	3000K		
	Osram	Philips	GE
MHC020	-	-	CMH20
MHC035	HC35CW	200006	-
MHC070	HC70CW	201676	-

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg