


## Spira



### LV Halogen




50w LVH GX5.3 ID942  LVH050

### MV Halogen

50w MVH GZ10 ID942  MVH050

### Metal Halide

35w MHB GX10 ID942  MHB035



- A** No control gear 240V (MVH)
- M** Electronic dimmable transformer
- N** Electronic dimmable transformer + Emergency
- P** 240/12V Transformer required
- Q** Electronic discharge ballast

- 1** - White **3** - Black **6** - Graphite

### Current and Power Ratings

Lamp	Watts (W)	Line 1 (A)
1x 50W	55.0	0.22

Lamp	Watts (W)	Line 1 (A)
1x 50W	50.0	0.21

Lamp	Watts (W)	Line 1 (A)
1x 35W	44.5	0.22

### Recommended Lamps

Type	Osram	Philips
LVH050	M258T	425164

Type	Osram	Philips
MVH050	P165FD	411792

Type	Sylvania
MHB035	0020270

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	<b>Uplighting</b> / Downlighting
	Uplighting / <b>Downlighting</b>
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg