



Liberté 435 Wall Light

Fluorescent

2x 18w PLC	G24q2	WL435 D	PLC218	-
2x 26w PLC	G24q3	WL435 D	PLC226	-

Current and Power Ratings

Lamp	Watts (W)	Line 1 (A)
2x 18W	40.0	0.190
2x 26W	56.0	0.260

Add 12W to Emergency versions for continuous charge

High frequency
 1 - White 3 - Black 4 - Chrome 6 - Graphite

Recommended Lamps

Type	3000K		4000K	
	Osram	Philips	Osram	Philips
PLC018	DDE183	623331	DDE184	623348
PLC026	DDE263	623355	DDE264	623362

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg