


## Liberte Plus

**Fluorescent**

10w PLC G24q-1 **WL438** **PLC010**



- Gear type F must be operated through a Digital Serial Interface (p389)**
  - B** Wire wound (MHL)
  - D** High frequency
  - E** High frequency + Emergency (WL438)
  - F** High frequency digital dimming
  - H** High frequency analogue (1-10V) dimming
  - J** High frequency switch dimming
  - S** High frequency DALI dimming
- } WL436
- 1** - White **3** - Black **6** - Graphite
  - I38** Instant light (MHL)

### Current and Power Ratings

PLC Lamp	Current (A)	Power (W)
1 x 10W	0.05	12.0

### Recommended Lamps

Type	3000K		4000K	
	Osram	Philips	Osram	Philips
PLC010	DDE103	623294	DDE104	623300

## Product Codes Explained



## Symbols

	12V
	Voltage & frequency
	Class I / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Unfused terminal block
	Fused terminal block
	Integral fuse
	Knockout size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	<b>Uplighting</b> / Downlighting
	Uplighting / <b>Downlighting</b>
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Injection moulding
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg