


Metropolis Cafe Wall Light

						Fascia	Light spill		
Fluorescent									
2x 14w	TFL	G5	600mm	WL891	-	TFL214	26	2	169
2x 24w	TFL	G5	600mm	WL891	-	TFL224	26	2	169



TFL

- Gear types F & G must be operated through a Digital Serial Interface
- D** High frequency
- E** High frequency + Emergency
- F** High frequency digital dimming
- G** High frequency digital dimming + Emergency
- H** High frequency analogue (1-10V) dimming
- I** High frequency analogue (1-10V) dimming + Emergency
- J** High frequency switch dimming
- K** High frequency switch dimming + Emergency

Current and Power Ratings

Lamp	D-K	
	Watts (W)	Line 1 (A)
2x 14W	32.0	0.15
2x 24W	51.0	0.22

Add 12W to Emergency versions for continuous charge

Recommended Lamps

Type	3000K		4200K	
	Osram	Philips	Osram	Philips
TFL014	FH1483	639387	FH1484	639400
TFL024	FH2483	639585	FH2484	639609

	12V
	Voltage & frequency
	Class 1 / II / III
	Ingress protection
	Suitable for flammable surface
	Plug & socket connections
	Fused terminal block
	Integral fuse
	Knock out size
	Tilt
	Rotation / pan
	Cut out
	Fixing centres
	Uplighting / Downlighting
	Uplighting / Downlighting
	Pressed metal construction
	Extruded aluminium construction
	Spun construction
	Die cast construction
	Minimum distance from lamp
	Decorative glass feature
	Safety glass
	Foot switch
	Supplied complete with plug
	Maximum weight kg
	Operating temperature of fascia
	Tamper proof screws
	Maximum evenly distributed load kg